


Profil P5XL

The P5XL has been developed to last against the continued increase of mechanisation in the vineyard. With a narrow cross section and increased steel fold on the rear of the post, the P5XL can pass easily through any type of mechanisation. This makes it easier to use all common harvest, pruning and under vine cleaning machines, reducing the risk of impact against the post. The large lateral walls of the post ensure exceptional ground stability and resistance to side pressure.

Our posts are available in 4 different types:

- Hot Dipped Galvanised
- Strip Galvanised (Z275)
- Zinc-Aluminium-Magnesium (ZM310)
- Weathering steel



P5XL Configuration table

Hooks	Post length [cm]	
	250-270	280-300
	Number of pairs of hooks	
10 mm short tapered S-hook	1	1
10 mm long tapered S-hook	7	7
10 mm R-hook	7	7
14 mm Combi-hook	7	7
10 mm short tapered S-hook	4	4
8 mm S-hook	1	3
8 mm Double hook	1	1
Total number of pairs of hooks	14	16

Installation depth table

Post length [cm]	Recommended installation depth [cm]	
250	70-75	
260	80	
270	85	
280	90	
300	95	

For intermediate posts the profile opening should always be facing the slope.



3-hook system: the right hook for each application

Upper fixed wire Short tapered S-hook Moving wire area Long tapered S-hook Combi-hook R-hook Short tapered S-hook Lower fixed wire S-hook Double hook

- Narrow width profile for ease of use with mechanisation.
- Increased rear fold to protect against mechanical impacts.
- Large side wall for lateral stability.
- Robust and reassuring profile
- Available in R, S and Combi Hook.

Profil Alsace S.A.S.

Zone Industrielle Kiesweg F-67630 Niederlauterbach Tel.: +33 (0) 3 88 94 68 88 Fax: +33 (0) 3 88 94 68 85 E-Mail: info@profilalsace.com www.profilalsace.com





Vebsite

Youtube